## EVAPCO, INC. UNIT MODEL # DWG. # SERIAL # **CLOSED CIRCUIT COOLER** NTS W2091210-ERC-RS ATC-DC-1012I-25-2EF 5/16/2024 NOTES: 1. (M)- FAN MOTOR LOCATION (M)**BOTTOM OUTLET** 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD 18 1/8 - 71 7/8 FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. + UNIT WEIGHT DOES NOT INCLUDE ⊡ ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 5. 3/4" DIA. MOUNTING HOLES. REFER TO 8'-5 1/2" RECOMMENDED STEEL SUPPORT 6. THE SPRAY PUMP SHOULD BE SIZED FOR 550 GPM AND 2.5 PSIG AT THE INLET CONNECTION 7. \*- APPROXIMATE DIMENSIONS DO NOT USE FACE 2 FOR PRE-FABRICATION OF CONNECTING **PIPING** 11'-11 3/4" FACE 1 **PLAN VIEW** 19 3/4 ACCESS DOOR 1 3/8 26 3/8 0 97 7/8 11 1/8 6 FPT (2) 4 BFW FLUID IN **INLET** (2) 1/2 FPT VENTS 34 1/2 12'-10" (2) 4 BFW FLUID OUT 5 1/8 56 1/8 8'-5 1/2" -- 11'-11 3/4" FACE 2 FACE 1 NO. OF SHIPPING SECTIONS SHIPPING OPERATING HEAVIEST SECTION lbs.+ 13920 19110 lbs. 12100 lbs 2 WEIGHT WEIGHT WEIGHT