EVAPCO, INC. UNIT MODEL # SERIAL # **CLOSED CIRCUIT COOLER** NTS W2244012-ERC-LFHR AT 456-5O26 5/17/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD 117 7/8 BFW DENOTES BEVELED FOR WELDING 4. + UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 5. 3/4" DIA. MOUNTING HOLES. REFER TO **--** 102 1/4 -- 1 RECOMMENDED STEEL SUPPORT 24'-1 1/8" 6. THE SPRAY PUMP SHOULD BE SIZED FOR 5600 GPM AND 2.5 PSIG AT THE INLET CONNECTION (4) 7. *- APPROXIMATE DIMENSIONS DO NOT USE **BOTTOM** FOR PRE-FABRICATION OF CONNECTING FACE 1 **PIPING OUTLET** 117 7/8 40'-2 1/2" FACE 2 **PLAN VIEW — 10 3/8** 22 1/4 19 3/4 --- 19 3/4[°] ACCESS DOOR ACCESS DOOR ACCESS (M) ACCESS (M) - 1 5/8 ₁₃₁ 1/8 1 5/8 (2) (2) 34 1/4 -34 1/4* (8) 1/2 FPT (8) 1/2 FPT (8) 4 BFW FLUID IN FLUID IN (8) 4 BFW 47 3/4 1 6 FPT 6 FPT **VENT VENT** 19'-1 1/4" FLUID OUT INLET INLET 5 1/4 98 1/8 24'-1 1/8" -40'-2 1/2" FACE 1 FACE 2 NO. OF SHIPPING SECTIONS SHIPPING OPERATING HEAVIEST SECTION 146540 lbs. 197020 32260 lbs 6 lbs. WEIGHT WEIGHT WEIGHT