UNIT CONDENSER						vanca <sup>®</sup>	DWG. # WB3TM2412-DRC-ST	REV.
10DEL #	eco-ATC-1002A	SCALE NTS	EVAP	CO, I	VC. E		SERIAL #	DATE 5/10/2024
2. HEAVII 3. MPT D FPT DE BFW D GVD D FLG DI PE DEI 4. +UNIT 4. +UNIT 5. MAKE- 20 psi I 6. *-APPF FOR P PIPING 7. 3/4" [15 RECON	IN MOTOR LOCATION EST SECTION IS UPPER SEC ENOTES MALE PIPE THREA ENOTES FEMALE PIPE THREA ENOTES BEVELED FOR WE ENOTES GROOVED ENOTES PLAINGE NOTES PLAIN END WEIGHT DOES NOT INCLUE ESORIES (SEE ACCESSORY UP WATER PRESSURE MIN [137 kPa], 50 psi MAX [34 ROXIMATE DIMENSIONS DO RE-FABRICATION OF CONNI ESTABLE SUPPORT SIONS LISTED AS FOLLOWS ENGLISH FT-IN METRIC [mm]	D EAD ELDING  DE DRAWINGS)  A kPa] NOT USE ECTING  S. REFER TO DRAWING.	7" [ 178]	FACI PLAN VIE		ACCESS DOOR  FAC	ACCESS DOOR	FACE D
(2) ½'-1 [64	3 5/8"	REFRIG OUT	- 2'-6 3/8" *	. 1 <sup>1</sup>	1'-3 1/4" [ 387 ]	11'-11 3/4" [ 3651]  FACE /		1'-5" [ 432]
SHIPPING WEIGHT	45120 lbs+ [204]	70] kg+	OPERATING 57760 lbs+ [	26200] kg+	HEAVIEST SECTION WEIGHT	20010 lbs+ [9080] kg+	NO. OF SHIPPING SECTIONS 4	DRAWN BY: SLR