



Low Charge Packaged Refrigeration Systems



The *natural evolution* of ammonia
refrigeration systems



for LIFE *An Employee Owned Company*





EVAPCO Global Headquarters, Taneytown, Maryland USA

Since its founding in 1976, EVAPCO, Incorporated has become an industry leader in the engineering and manufacturing of quality heat transfer products around the world. EVAPCO's mission is to provide first class service and quality products for the following markets:

- Industrial Refrigeration
- Commercial HVAC
- Industrial Process
- Power

Evapcold® is manufactured in Greenup, IL, in a new 100,000 sq. ft. building dedicated to the assembly of all components required for the Evapcold system. The Evapcold manufacturing operation utilizes a lean assembly line process which provides fabrication and assembly in the most efficient way possible with the highest quality and shortest lead time.



Evapcold Manufacturing, Greenup, Illinois



The Perfect Solution

Expanding government regulations and industry codes are adversely impacting users of ammonia refrigeration systems and restricting the use of possible alternative refrigerants. These regulations and codes are making it increasingly difficult and cost-prohibitive to add cold storage capacity or process rooms to existing facilities due to the impact on the total system charge. Minimizing the total system charge is now a key objective for many owners and operators who are evaluating the refrigeration system design for new warehouse and food processing facilities.

EVAPCO has developed the perfect solution to address these challenges...the **NEW Evapcold Low Charge Refrigeration (LCR)** product line. With over 250 models available in the initial product launch, Evapcold packaged systems provide the required refrigeration while significantly reducing ammonia charge, total cost of ownership and the perceived risk associated with conventional systems today.

The Evapcold LCR product line features a pumped liquid ammonia refrigeration system consisting of highest quality, industry-recognized components and new innovative technologies engineered specifically for low charge package systems. Evapcold is the first in a series of low charge refrigeration products which EVAPCO will be developing to meet the current and future needs of the industrial refrigeration industry.

The Evapcold product is another example of EVAPCO's commitment to use its industry leading research and development capabilities to develop product solutions which make life simpler, more reliable and more sustainable for you.

PRODUCT APPLICATIONS

- 10 TR to 100 TR Capacity
- -20F° to +50F° Room Temperature
- Water-Cooled or Air-Cooled Condensing
- Roof Mounted Design for Efficient Cooling

The Evapcold product line has been engineered by a team of industry experts with over 200 years of professional experience in screw compressor packaging, ammonia system engineering, microprocessor controls technology, field construction and system commissioning. In addition, every Evapcold packaged ammonia system combines innovative patent-pending technology with the highest quality ammonia screw compressors, heat exchangers, valves, controls and piping to ensure efficient system operation and reliability with the lowest possible refrigerant charge.

The advantage of Evapcold manufactured refrigerant systems is further enhanced by EVAPCO's ability to perform actual full scale unit testing in a wide range of environmental conditions. The Evapcold product and components have been tested in -35°F to 100°F ambient temperature conditions in the Wilson E. Bradley R&D Center, located at EVAPCO World Headquarters in Taneytown, MD.

Evapcold testing includes verification of many operational parameters under a wide range of conditions as shown below:

- **Thermal Performance (Cooling and Heat Rejection Capacity)**
- **Total Energy Consumption (kW) and Component Optimization**
- **Refrigerant Charge Volume**
- **Refrigerant Recirculation Rate**
- **Operational Excursions including Cold and Hot Starts**

The result of this extensive testing is Evapcold, an "evolutionary" low charge packaged ammonia refrigeration system, expertly designed with proven system components and patent-pending technology. Evapcold offers single-source responsibility for the complete system design, thermal performance, in-house factory-assembly and testing. This ensures simplified design and installation, easy start-up, reliable operation and peace of mind safety.



Evapcold units in the Wilson E. Bradley R&D Center, Taneytown, MD




Evapcold R & D Test Stand



The Natural Leader in Complete Self-

Single-Source Responsibility for Complete Design, Factory Assembly, Operation and



Water-Cooled & Air-Cooled Models Available

(Air-Cooled Shown: Model # LCR-60P-L20-2-H-W)

Touch Screen HMI Control Panel




Main Control Panel – Interior View



Exterior Service Panel

Complete Packaged Machine Room With Patent Pending System Technology




Factory assembled and tested machine room module

Optional Penthouse Ductwork (alternative configurations available)

Contained Low Charge Ammonia Refrigeration Systems

System Safety



- Penthouse module features evaporators with EVAPCO low charge technology.
- Evaporator performance rated in accordance with AHRI Standard 420.
- Two 50% capacity coils provided in Low & Medium Temperature models for defrost control.

Overhead view of machine room and penthouse modules.

FEATURES AND BENEFITS

- Engineered in accordance with industry codes including: IIAR, ASHRAE, IBC, IMC, IFC, UMC, OSHA, NEC and ASME
- True "plug & play" design simplifies installation, start-up and commissioning
- Significantly reduces system ammonia charge to approximately 3 lb./TR
- Compact design reduces piping and eliminates components typically found in high charge systems
- Innovative walk-in machine room design incorporates all safety & access requirements.
- High quality screw compressors, valves, controls and piping (95% of system piping is 304 stainless steel).
- Low 1.2 : 1.0 recirculation rate for optimum evaporator performance.
- Pumped ammonia liquid feed design for reliable and stable operation.
- Direct refrigerant to air cooling coil for maximum efficiency.
- Variable speed screw compressor operation for maximum efficiency.
- System control with industry leading microprocessor technology designed specifically for low charge refrigerant systems.


Innovative insulated machine room floor for installation over refrigerated space



Typical Applications & Benefits



LCR Water Cooled Design




LCR units shown with cooling water piping from cooling tower or fluid cooler

Water Cooled Design Benefits

- Provides maximum energy efficiency and lowest refrigerant charge
- No ammonia field piping

Evapcold Applications Include:

- Cold storage or process room expansions
- New cold storage and distribution facilities
 - Designed with a 100% Evapcold LCR product solution
 - Hybrid system with Evapcold LCR units and a smaller conventional field-erected system




LCR Air Cooled Design

Air Cooled Design Benefits

- Zero water usage
- Eliminates cooling tower and associated water piping
- Complete self-contained units*
- Optional adiabatic pads available for improved efficiency with minimal water usage


*Air-cooled condenser ships loose

HIGH TEMPERATURE UNITS




DIMENSIONS (all units) (ft.-in.)		
L	W	H
(See Unit)	10' 10"	9' 7"


NOMINAL CAPACITIES		LCR MODEL RANGE
TR Range	Room Temp. Range	
10 TR to 14 TR	35°F to 55°F	LCR-10P-H25 thru LCR-10P-H40



NOMINAL CAPACITIES		LCR MODEL RANGE
TR Range	Room Temp. Range	
15 TR to 29 TR	35°F to 55°F	LCR-15P-H25 thru LCR-25P-H40




NOMINAL CAPACITIES		LCR MODEL RANGE
TR Range	Room Temp. Range	
30 TR to 39 TR	35°F to 55°F	LCR-30P-H25 thru LCR-30P-H40




NOMINAL CAPACITIES		LCR MODEL RANGE
TR Range	Room Temp. Range	
40 TR to 100 TR	35°F to 55°F	LCR-50P-H25 thru LCR-100P-H40

MEDIUM & LOW TEMPERATURE UNITS




DIMENSIONS (all units) (ft.-in.)		
L	W	H
(See Unit)	10' 10"	9' 7"

NOMINAL CAPACITIES		LCR MODEL RANGE
TR Range	Room Temp. Range	
10 TR to 35 TR	5°F to 35°F	LCR-10P-M0 thru LCR-30P-M25
10 TR to 35 TR	(-)20°F to 5°F	LCR-10P-L30 thru LCR-30P-L5



NOMINAL CAPACITIES		LCR MODEL RANGE
TR Range	Room Temp. Range	
35 TR to 60 TR	5°F to 35°F	LCR-40P-M0 thru LCR-50P-M25
35 TR to 55 TR	(-)20°F to 5°F	LCR-40P-L30 thru LCR-50P-L5
55 TR to 65 TR	(-)20°F to 5°F	LCR-60P-L30 thru LCR-60P-L5
60 TR to 75 TR	5°F to 35°F	LCR-70P-M0 thru LCR-70P-M25



NOMINAL CAPACITIES		LCR MODEL RANGE
TR Range	Room Temp. Range	
75 TR to 95 TR	5°F to 35°F	LCR-90P-M0 thru LCR-90P-M25

Note: Tables and figures shown above are nominal ratings and based on water-cooled units and 95°F condensing temperature. Please consult factory for ratings and selections.

EVAPCOLD MODEL NOMENCLATURE

FAMILY	NOMINAL CAPACITY (TR)	CONFIGURATION	DUTY	EVAPORATOR TEMP. (°F)	NUMBERS OF COILS	DEFROST	CONDENSING
LCR	XXX	P	L	XX	2	H	W
						A	W WATER COOLED CONDENSING
						H	A AIR COOLED CONDENSING
						N	H HOT GAS DEFROST
							N NO DEFROST
					1		1 COIL
					2		2 COIL
							EVAPORATOR REFRIGERANT TEMPERATURE ("L" Duty denotes negative temp.)
							L LOW TEMP ECONOMIZED
							M MEDIUM TEMP ECONOMIZED
							H HIGH TEMP NON-ECONOMIZED
							P PENTHOUSE PACKAGE SOLUTION
							Low Charge Refrigeration



★ World Headquarters/
Research and
Development Center

■ EVAPCO Facilities

EVAPCO, Inc. — World Headquarters & Research/Development Center

EVAPCO, Inc. • P.O. Box 1300 • Westminster, MD 21158 USA
PHONE: 410-756-2600 • FAX: 410-756-6450 • E-MAIL: marketing@evapco.com

EVAPCO North America

**EVAPCO, Inc.
World Headquarters**
P.O. Box 1300
Westminster, MD 21158 USA
Phone: 410-756-2600
Fax: 410-756-6450
E-mail: marketing@evapco.com

EVAPCO East
5151 Allendale Lane
Taneytown, MD 21787 USA
Phone: 410-756-2600
Fax: 410-756-6450
E-mail: marketing@evapco.com

EVAPCO Midwest
1723 York Road
Greenup, IL 62428 USA
Phone: 217-923-3431
Fax: 217-923-3300
E-mail: evapcomw@evapcomw.com

EVAPCO West
1900 West Almond Avenue
Madera, CA 93637 USA
Phone: 559-673-2207
Fax: 559-673-2378
E-mail: contact@evapcowest.com

EVAPCO Iowa
925 Quality Drive
Lake View, IA 51450 USA
Phone: 712-657-3223
Fax: 712-657-3226

**EVAPCO Iowa
Sales & Engineering**
215 1st Street, NE
P.O. Box 88
Medford, MN 55049 USA
Phone: 507-446-8005
Fax: 507-446-8239
E-mail: evapcomn@evapcomn.com

EVAPCO Newton
701 East Jourdan Street
Newton, IL 62448 USA
Phone: 618-783-3433
Fax: 618-783-3499
E-mail: evapcomw@evapcomw.com

evapcold
EVAPCOLD Manufacturing
521 Evapco Drive
Greenup, IL 62428 USA
Phone: 217-923-3431
E-mail: evapcomw@evapcomw.com

EVAPCO-BLCT Dry Cooling, Inc.
1011 US Highway 22 West
Bridgewater, New Jersey 08807 USA
Phone: 1-908-379-2665
E-mail: info@evapco-blct.com

**Refrigeration Valves &
Systems Corporation**
A wholly owned subsidiary of EVAPCO, Inc.
1520 Crosswind Dr.
Bryan, TX 77808 USA
Phone: 979-778-0095
Fax: 979-778-0030
E-mail: rvs@rvscorp.com

EVAPCO Northwest
5775 S.W. Jean Road, Suite 104
Lake Oswego, Oregon 97035 USA
Phone: 503-639-2137
Fax: 503-639-1800

EvapTech, Inc.
A wholly owned subsidiary of EVAPCO, Inc.
8331 Nieman Road
Lenexa, KS 66214 USA
Phone: 913-322-5165
Fax: 913-322-5166
E-mail: marketing@evaptech.com

Tower Components, Inc.
A wholly owned subsidiary of EVAPCO, Inc.
5960 US HWY 64E
Ramseur, NC 27316
Phone: 336-824-2102
Fax: 336-824-2190
E-mail: mail@towercomponentsinc.com

EVAPCO South America

EVAPCO SEMCO
Equipamentos de Refrigeraçao Ltda.
Rua Alexandre Dumas, 1601 - 2 andar
04717-004 Sao Paulo - SP - Brazil
Phone: (55) 11-5184-0067

EVAPCO Europe

**EVAPCO Europe BVBA
European Headquarters**
Industrieterrein Oost 4010
3700 Tongeren, Belgium
Phone: (32) 12-395029
Fax: (32) 12-238527
E-mail: evapco.europe@evapco.be

EVAPCO Europe, S.r.l.
Via Ciro Menotti 10
I-20017 Passirana di Rho
Milan, Italy
Phone: (39) 02-939-9041
Fax: (39) 02-935-00840
E-mail: evapcoeuropa@evapco.it

EVAPCO Europe, S.r.l.
Via Dosso 2
23020 Piateda Sondrio, Italy

EVAPCO Europe GmbH
Meerbuscher Straße 64-78
Haus 5
40670 Meerbusch, Germany
Phone: (49) 2159-69560
Fax: (49) 2159-695611
E-mail: info@evapco.de

Flex coil a/s
A wholly owned subsidiary of EVAPCO, Inc.
Knøsgårdvej 115
DK-9440 Aabybro Denmark
Phone: (45) 9824 4999
Fax: (45) 9824 4990
E-mail: info@flexcoil.dk

EVAPCO S.A. (Pty.) Ltd.
A licensed manufacturer of EVAPCO, Inc.
18 Quality Road
Isando 1600
Republic of South Africa
Phone: (27) 11-392-6630
Fax: (27) 11-392-6615
E-mail: evapco@evapco.co.za

Evap Egypt Engineering Industries Co.
A licensed manufacturer of EVAPCO, Inc.
5 El Nasr Road
Nasr City, Cairo, Egypt
Phone: 2 02 24022866/2 02 24044997
Fax: 2 02 24044667/2 02 24044668
E-mail: Primacool@link.net/Shady@primacool.net

EVAPCO Asia/Pacific

EVAPCO Asia/Pacific Headquarters
1159 Luoning Rd. Baoshan Industrial Zone
Shanghai, P. R. China, Postal Code: 200949
Phone: (86) 21-6687-7786
Fax: (86) 21-6687-7008
E-mail: marketing@evapcochina.com

**EVAPCO (Shanghai) Refrigeration
Equipment Co., Ltd.**
1159 Luoning Rd., Baoshan Industrial Zone
Shanghai, P.R. China, Postal Code: 200949
Phone: (86) 21-6687-7786
Fax: (86) 21-6687-7008
E-mail: marketing@evapcochina.com

**Beijing EVAPCO Refrigeration
Equipment Co., Ltd.**
Yan Qi Industrial Development District
Huai Rou County
Beijing, P.R. China, Postal Code: 101407
Phone: (86) 10 6166-7238
Fax: (86) 10 6166-7395
E-mail: evapcobj@evapcochina.com

EVAPCO Australia (Pty.) Ltd.
34-42 Melbourne Road
P.O. Box 436
Riverstone, N.S.W. Australia 2765
Phone: (61) 2 9627-3322
Fax: (61) 2 9627-1715
E-mail: sales@evapco.com.au

EVAPCO Composites Sdn. Bhd
No. 70 (Lot 1289) Jalan Industri 2/3
Rawang Integrated Industrial Park
Rawang, Selangor, 48000 Malaysia
Phone: 60 3 6092-2209
Fax: 60 3 6092-2210

EvapTech Asia Pacific Sdn. Bhd
A wholly owned subsidiary of EvapTech, Inc.
B-6-1, IOI Boulevard
Jalan Kenari 5, Bandar Puchong Jaya
47170 Puchong, Selangor Darul Ehsan
Malaysia
Phone: (60-3) 8070-7255
Fax: (60-3) 8070-5731
E-mail: marketing-ap@evaptech.com

EVAPCOLD...Low Charge Packaged Ammonia Refrigeration Systems

Visit EVAPCOLD Website at: www.evapcold.com

