INFER DIP FAME UCCATION INF PAME OF UCCATIO	UNIT COOLING TOWER	EVADO INIO EVODO - AX142420-DRA-ST
ACCESSION FACE		
11'-4 1/4" 11'-4 1/4" 22'-6 7/8" [6880] 22'-6 7/8" 22'-6 7/8" 22'-6 7/8" 37/8" 11'-2 5/8" 37/8" 14' [350] BFW/GVD OUTLET 10'-3" ACCESS DOOR 4' [100] FPT OVERFLOW 37 [80] MPT MAKE-UP 4' [100] FPT OUTLET 11'-1" 13'-11 1/4" 11'-1" 13378] 12'-4 1/2" 12'-4 1/2" 17544] FACE B	BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 6. 3/4" DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 7. DIMENSIONS LISTED AS FOLLOWS: ENGLISH IN	FACE B PLAN VIEW FACE D PLAN VIEW 10
HIPPING PERATING HEAVIEST SECTION NO. OF SHIPPING SECTIONS DRAWN BY: 0.5	13'-11 1/4"	11'-4 1/4" 3462] 11'-4 1/4" 3468] 11'-2 5/8" 3418] 37/8" 10' 3" 10' 3" 11'-17/8" 12'-4 1/2" 11'-17/8" 12'-4 1/2" 12'-4 1/2" 12'-4 1/2" 12'-4 1/2" 17'-544]
WEIGHT 23210 lbs+ [10530] kg+ WEIGHT 49860 lbs+ [22620] kg+ WEIGHT 13450 lbs+ [6105] kg+ WEIGHT 2 SLR	SHIPPING WEIGHT 23210 lbs+ [10530] kg+	OPERATING ACCOUNT TOOCOGY HEAVIEST SECTION ACATE IN 194 TO TOO OF SHIPPING SECTIONS 2 DRAWN BY: SLD